


starting out with >>>

C++

From Control Structures through Objects

EIGHTH EDITION

Chapter 3: Expressions and Interactivity



TONY GADDIS

Addison-Wesley
3rd printing of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

starting out with >>>

C++

From Control Structures through Objects

EIGHTH EDITION

3.1

The `cin` Object

Addison-Wesley
3rd printing of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

The `cin` Object

- Standard input object
- Like `cout`, requires `iostream` file
- Used to read input from keyboard
- Information retrieved from `cin` with `>>`
- Input is stored in one or more variables

Addison-Wesley
3rd printing of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

The `cin` Object in Program 3-1

```

Program 3-1
1 // This program asks the user to enter the length and width of
2 // a rectangle. It calculates the rectangle's area and displays
3 // the value on the screen.
4 #include <iostream>
5 using namespace std;
6
7 int main()
8 {
9     int length, width, area;
10
11     cout << "This program calculates the area of a ";
12     cout << "rectangle.\n";
13     cout << "What is the length of the rectangle? ";
14     cin >> length;
15     cout << "What is the width of the rectangle? ";
16     cin >> width;
17     area = length * width;
18     cout << "The area of the rectangle is " << area << ".\n";
19     return 0;
20 }

```

Program Output with Example Input Shown in Bold
This program calculates the area of a rectangle.
What is the length of the rectangle? **10** [Enter]
What is the width of the rectangle? **20** [Enter]
The area of the rectangle is 200.

Addison-Wesley
3rd printing of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

The `cin` Object

- `cin` converts data to the type that matches the variable:

```

int height;
cout << "How tall is the room? ";
cin >> height;

```

Addison-Wesley
3rd printing of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Displaying a Prompt

- A prompt is a message that instructs the user to enter data.
- You should always use `cout` to display a prompt before each `cin` statement.

```

cout << "How tall is the room? ";
cin >> height;

```

Addison-Wesley
3rd printing of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

The cin Object

- Can be used to input more than one value:
cin >> height >> width;
- Multiple values from keyboard must be separated by spaces
- Order is important: first value entered goes to first variable, etc.

Addison-Wesley
Learning Technology

PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

The cin Object Gathers Multiple Values in Program 3-2

Program 3-2

```

1 // This program asks the user to enter the length and width of
2 // a rectangle. It calculates the rectangle's area and displays
3 // the value on the screen.
4 #include <iostream>
5 using namespace std;
6
7 int main()
8 {
9     int length, width, area;
10
11     cout << "This program calculates the area of a ";
12     cout << "rectangle.\n";
13     cout << "Enter the length and width of the rectangle ";
14     cout << "separated by a space.\n";
15     cin >> length >> width;
16     area = length * width;
17     cout << "The area of the rectangle is " << area << endl;
18     return 0;
19 }

```

Program Output with Example Input Shown in Bold
 This program calculates the area of a rectangle.
 Enter the length and width of the rectangle separated by a space.
10 20 [Enter]
 The area of the rectangle is 200

Addison-Wesley
Learning Technology

PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

The cin Object Reads Different Data Types in Program 3-3

Program 3-3

```

1 // This program demonstrates how cin can read multiple values
2 // of different data types.
3 #include <iostream>
4 using namespace std;
5
6 int main()
7 {
8     int whole;
9     double fractional;
10    char letter;
11
12    cout << "Enter an integer, a double, and a character: ";
13    cin >> whole >> fractional >> letter;
14    cout << "Whole: " << whole << endl;
15    cout << "Fractional: " << fractional << endl;
16    cout << "Letter: " << letter << endl;
17    return 0;
18 }

```

Program Output with Example Input Shown in Bold
 Enter an integer, a double, and a character: **4 5.7 b [Enter]**
 Whole: 4
 Fractional: 5.7
 Letter: b

Addison-Wesley
Learning Technology

PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

3.2

Mathematical Expressions

Addison-Wesley
Learning Technology

PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Mathematical Expressions

- Can create complex expressions using multiple mathematical operators
- An expression can be a literal, a variable, or a mathematical combination of constants and variables
- Can be used in assignment, cout, other statements:

```

area = 2 * PI * radius;
cout << "border is: " << 2*(l+w);

```

Addison-Wesley
Learning Technology

PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Order of Operations

In an expression with more than one operator, evaluate in this order:

- (unary negation), in order, left to right
- * / %, in order, left to right
- + -, in order, left to right

In the expression $2 + 2 * 2 - 2$

evaluate second evaluate first evaluate third

Addison-Wesley
Learning Technology

PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Order of Operations

Table 3-2 Some Simple Expressions and Their Values

Expression	Value
$5 + 2 * 4$	13
$10 / 2 - 3$	2
$8 + 12 * 2 - 4$	28
$4 + 17 \% 2 - 1$	4
$6 - 3 * 2 + 7 - 1$	6

Addison-Wesley
is an imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Associativity of Operators

- $-$ (unary negation) associates right to left
- $*$, $/$, $\%$, $+$, $-$ associate right to left
- parentheses $()$ can be used to override the order of operations:

$$2 + 2 * 2 - 2 = 4$$

$$(2 + 2) * 2 - 2 = 6$$

$$2 + 2 * (2 - 2) = 2$$

$$(2 + 2) * (2 - 2) = 0$$

Addison-Wesley
is an imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Grouping with Parentheses

Table 3-4 More Simple Expressions and Their Values

Expression	Value
$(5 + 2) * 4$	28
$10 / (5 - 3)$	5
$8 + 12 * (6 - 2)$	56
$(4 + 17) \% 2 - 1$	0
$(6 - 3) * (2 + 7) / 3$	9

Addison-Wesley
is an imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Algebraic Expressions

- Multiplication requires an operator:
 $Area=lw$ is written as $Area = l * w$;
- There is no exponentiation operator:
 $Area=s^2$ is written as $Area = pow(s, 2)$;
- Parentheses may be needed to maintain order of operations:

$$m = \frac{y_2 - y_1}{x_2 - x_1} \quad \text{is written as} \quad m = (y_2 - y_1) / (x_2 - x_1);$$

Addison-Wesley
is an imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Algebraic Expressions

Table 3-5 Algebraic and C++ Multiplication Expressions

Algebraic Expression	Operation	C++ Equivalent
$6B$	6 times B	$6 * B$
$(3)(12)$	3 times 12	$3 * 12$
$4xy$	4 times x times y	$4 * x * y$

Addison-Wesley
is an imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

3.3

When You Mix Apples with Oranges: Type Conversion



Addison-Wesley
is an imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

When You Mix Apples with Oranges: Type Conversion

- Operations are performed between operands of the same type.
- If not of the same type, C++ will convert one to be the type of the other
- This can impact the results of calculations.

Addison-Wesley
3 as an imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Hierarchy of Types

Highest: long double
double
float
unsigned long
long
unsigned int
int

Lowest:

Ranked by largest number they can hold

Addison-Wesley
3 as an imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Type Coercion

- Type Coercion: automatic conversion of an operand to another data type
- Promotion: convert to a higher type
- Demotion: convert to a lower type

Addison-Wesley
3 as an imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Coercion Rules

- 1) char, short, unsigned short automatically promoted to int
- 2) When operating on values of different data types, the lower one is promoted to the type of the higher one.
- 3) When using the = operator, the type of expression on right will be converted to type of variable on left

Addison-Wesley
3 as an imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

3.4

Overflow and Underflow

Addison-Wesley
3 as an imprint of
PEARSON


Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Overflow and Underflow

- Occurs when assigning a value that is too large (overflow) or too small (underflow) to be held in a variable
- Variable contains value that is 'wrapped around' set of possible values
- Different systems may display a warning/error message, stop the program, or continue execution using the incorrect value

Addison-Wesley
3 as an imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.



3.5

Type Casting

Addison-Wesley
3rd printing of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Type Casting

- Used for manual data type conversion
- Useful for floating point division using ints:


```
double m;
m = static_cast<double>(y2-y1)
    / (x2-x1);
```
- Useful to see int value of a char variable:


```
char ch = 'C';
cout << ch << " is "
    << static_cast<int>(ch);
```

Addison-Wesley
3rd printing of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Type Casting in Program 3-9

Program 3-9

```
1 // This program uses a type cast to avoid integer division.
2 #include <iostream>
3 using namespace std;
4
5 int main()
6 {
7     int books;           // Number of books to read
8     int months;         // Number of months spent reading
9     double perMonth;    // Average number of books per month
10
11     cout << "How many books do you plan to read? ";
12     cin >> books;
13     cout << "How many months will it take you to read them? ";
14     cin >> months;
15     perMonth = static_cast<double>(books) / months;
16     cout << "That is " << perMonth << " books per month.\n";
17     return 0;
18 }
```

Program Output with Example Input Shown in Bold
How many books do you plan to read? **30** [Enter]
How many months will it take you to read them? **7** [Enter]
That is 4.28571 books per month.

Addison-Wesley
3rd printing of
PEARSON


Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

C-Style and Prestandard Type Cast Expressions

- C-Style cast: data type name in ()
cout << ch << " is " << (int)ch;
- Prestandard C++ cast: value in ()
cout << ch << " is " << int(ch);
- Both are still supported in C++, although static_cast is preferred

Addison-Wesley
3rd printing of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.



3.6

Multiple Assignment and Combined Assignment

Addison-Wesley
3rd printing of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Multiple Assignment and Combined Assignment

- The = can be used to assign a value to multiple variables:


```
x = y = z = 5;
```
- Value of = is the value that is assigned
- Associates right to left:


```
x = (y = (z = 5));
```

value is 5 value is 5 value is 5

Addison-Wesley
3rd printing of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Combined Assignment

- Look at the following statement:

```
sum = sum + 1;
```

This adds 1 to the variable **sum**.

Addison-Wesley
3 as imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Other Similar Statements

Table 3-8 (Assume $x = 6$)

Statement	What It Does	Value of x After the Statement
$x = x + 4;$	Adds 4 to x	10
$x = x - 3;$	Subtracts 3 from x	3
$x = x * 10;$	Multiplies x by 10	60
$x = x / 2;$	Divides x by 2	3
$x = x \% 4$	Makes x the remainder of $x / 4$	2

Addison-Wesley
3 as imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Combined Assignment

- The combined assignment operators provide a shorthand for these types of statements.

- The statement

```
sum = sum + 1;
```

is equivalent to

```
sum += 1;
```

Addison-Wesley
3 as imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Combined Assignment Operators

Table 3-9

Operator	Example Usage	Equivalent to
$++$	$x ++ 5;$	$x = x + 5;$
$--$	$y -- 2;$	$y = y - 2;$
$+=$	$z += 10;$	$z = z + 10;$
$/=$	$a /= b;$	$a = a / b;$
$\% =$	$c \% 3;$	$c = c \% 3;$

Addison-Wesley
3 as imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

3.7

Formatting Output



Addison-Wesley
3 as imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Formatting Output

- Can control how output displays for numeric, string data:

- size
- position
- number of digits

- Requires `iomanip` header file

Addison-Wesley
3 as imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Stream Manipulators

- Used to control how an output field is displayed
- Some affect just the next value displayed:
 - `setw(x)`: print in a field at least `x` spaces wide. Use more spaces if field is not wide enough

Addison-Wesley
Learning Technology

PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

The `setw` Stream Manipulator in Program 3-13

Program 3-13

```
1 // This program displays three rows of numbers.
2 #include <iostream>
3 #include <iomanip> // Required for setw
4 using namespace std;
5
6 int main()
7 {
8     int num1 = 2897, num2 = 5, num3 = 837,
9       num4 = 34, num5 = 7, num6 = 1623,
10      num7 = 390, num8 = 3456, num9 = 12;
11
12     // Display the first row of numbers
13     cout << setw(6) << num1 << setw(6)
14          << num2 << setw(6) << num3 << endl;
15
16     // Display the second row of numbers
17     cout << setw(6) << num4 << setw(6)
18          << num5 << setw(6) << num6 << endl;
19
20     // Display the third row of numbers
21     cout << setw(6) << num7 << setw(6)
22          << num8 << setw(6) << num9 << endl;
23     return 0;
24 }
```

Continued...

Addison-Wesley
Learning Technology

PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

The `setw` Stream Manipulator in Program 3-13

Program Output

```
2897 5 837
 34 7 1623
390 3456 12
```

Addison-Wesley
Learning Technology

PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Stream Manipulators

- Some affect values until changed again:
 - `fixed`: use decimal notation for floating-point values
 - `setprecision(x)`: when used with `fixed`, print floating-point value using `x` digits after the decimal. Without `fixed`, print floating-point value using `x` significant digits
 - `showpoint`: always print decimal for floating-point values

Addison-Wesley
Learning Technology

PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

More Stream Manipulators in Program 3-17

Program 3-17

```
1 // This program asks for sales figures for 3 days. The total
2 // sales are calculated and displayed in a table.
3 #include <iostream>
4 #include <iomanip>
5 using namespace std;
6
7 int main()
8 {
9     double day1, day2, day3, total;
10
11     // Get the sales for each day.
12     cout << "Enter the sales for day 1: ";
13     cin >> day1;
14     cout << "Enter the sales for day 2: ";
15     cin >> day2;
16     cout << "Enter the sales for day 3: ";
17     cin >> day3;
18
19     // Calculate the total sales.
20     total = day1 + day2 + day3;
```

Continued...

Addison-Wesley
Learning Technology

PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

More Stream Manipulators in Program 3-17

```
21 // Display the sales figures.
22 cout << "\nSales Figures\n";
23 cout << "-----\n";
24 cout << "setprecision(2) << fixed;
25 cout << "Day 1: " << setw(8) << day1 << endl;
26 cout << "Day 2: " << setw(8) << day2 << endl;
27 cout << "Day 3: " << setw(8) << day3 << endl;
28 cout << "Total: " << setw(8) << total << endl;
29 return 0;
30
31 }
```

Program Output with Example Input Shown in Bold

```
Enter the sales for day 1: 1321.87 [Enter]
Enter the sales for day 2: 1869.26 [Enter]
Enter the sales for day 3: 1403.77 [Enter]
```

```
Sales Figures
-----
Day 1: 1321.87
Day 2: 1869.26
Day 3: 1403.77
Total: 4594.90
```

Addison-Wesley
Learning Technology

PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Stream Manipulators

Table 3-12

Stream Manipulator	Description
<code>setw(n)</code>	Establishes a print field of n spaces.
<code>fixed</code>	Displays floating-point numbers in fixed point notation.
<code>showpoint</code>	Causes a decimal point and trailing zeroes to be displayed, even if there is no fractional part.
<code>setprecision(n)</code>	Sets the precision of floating-point numbers.
<code>left</code>	Causes subsequent output to be left justified.
<code>right</code>	Causes subsequent output to be right justified.

Addison-Wesley
Learning Technology

PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

3.8

Working with Characters and string Objects

Addison-Wesley
Learning Technology

PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Working with Characters and string Objects

- Using `cin` with the `>>` operator to input strings can cause problems:
- It passes over and ignores any leading *whitespace characters (spaces, tabs, or line breaks)*
- To work around this problem, you can use a C++ function named `getline`.

Addison-Wesley
Learning Technology

PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Using `getline` in Program 3-19

Program 3-19

```
1 // This program demonstrates using the getline function
2 // to read character data into a string object.
3 #include <iostream>
4 #include <string>
5 using namespace std;
6
7 int main()
8 {
9     string name;
10    string city;
11
12    cout << "Please enter your name: ";
13    getline(cin, name);
14    cout << "Enter the city you live in: ";
15    getline(cin, city);
16
17    cout << "Hello, " << name << endl;
18    cout << "You live in " << city << endl;
19    return 0;
20 }
```

Program Output with Example Input Shown in Bold

```
Please enter your name: Kate Smith [Enter]
Enter the city you live in: Raleigh [Enter]
Hello, Kate Smith
You live in Raleigh
```

Addison-Wesley
Learning Technology

PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Working with Characters and string Objects

- To read a single character:
 - Use `cin`:


```
char ch;
cout << "Strike any key to continue";
cin >> ch;
```

 Problem: will skip over blanks, tabs, `<CR>`
 - Use `cin.get()`:


```
cin.get(ch);
```

 Will read the next character entered, even whitespace

Addison-Wesley
Learning Technology

PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Using `cin.get()` in Program 3-21

Program 3-21

```
1 // This program demonstrates three ways
2 // to use cin.get() to pause a program.
3 #include <iostream>
4 using namespace std;
5
6 int main()
7 {
8     char ch;
9
10    cout << "This program has paused. Press Enter to continue.";
11    cin.get(ch);
12    cout << "It has paused a second time. Please press Enter again.";
13    ch = cin.get();
14    cout << "It has paused a third time. Please press Enter again.";
15    cin.get();
16    cout << "Thank you!";
17    return 0;
18 }
```

Program Output with Example Input Shown in Bold

```
This program has paused. Press Enter to continue. [Enter]
It has paused a second time. Please press Enter again. [Enter]
It has paused a third time. Please press Enter again. [Enter]
Thank you!
```

Addison-Wesley
Learning Technology

PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Working with Characters and string Objects

- Mixing `cin >>` and `cin.get()` in the same program can cause input errors that are hard to detect
- To skip over unneeded characters that are still in the keyboard buffer, use `cin.ignore()`:


```
cin.ignore(); // skip next char
cin.ignore(10, '\n'); // skip the next
// 10 char. or until a '\n'
```

Addison-Wesley
is an imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley All rights reserved.

string Member Functions and Operators

- To find the length of a string:


```
string state = "Texas";
int size = state.length();
```
- To concatenate (join) multiple strings:

```
greeting2 = greeting1 + name1;
greeting1 = greeting1 + name2;
```

Or using the `+=` combined assignment operator:

```
greeting1 += name2;
```

Addison-Wesley
is an imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley All rights reserved.

3.9

More Mathematical Library Functions

Addison-Wesley
is an imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley All rights reserved.

More Mathematical Library Functions

- Require `cmath` header file
- Take `double` as input, return a `double`
- Commonly used functions:

<code>sin</code>	Sine
<code>cos</code>	Cosine
<code>tan</code>	Tangent
<code>sqrt</code>	Square root
<code>log</code>	Natural (e) log
<code>abs</code>	Absolute value (takes and returns an int)

Addison-Wesley
is an imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley All rights reserved.

More Mathematical Library Functions

- These require `cstdlib` header file
- `rand()`: returns a random number (`int`) between 0 and the largest `int` the compute holds. Yields same sequence of numbers each time program is run.
- `srand(x)`: initializes random number generator with `unsigned int x`

Addison-Wesley
is an imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley All rights reserved.

3.10

Hand Tracing a Program

Addison-Wesley
is an imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley All rights reserved.

Hand Tracing a Program

- Hand trace a program: act as if you are the computer, executing a program:
 - step through and 'execute' each statement, one-by-one
 - record the contents of variables after statement execution, using a hand trace chart (table)
- Useful to locate logic or mathematical errors

Addison-Wesley
3x51mp1r1of

PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Program 3-27 with Hand Trace Chart

Program 3-27 (with hand trace chart filled)

```

1 // This program asks for three numbers, then
2 // displays the average of the numbers.
3 #include <iostream>
4 using namespace std;
5 int main()
6 {
7     double num1, num2, num3, avg;
8     cout << "Enter the first number: ";
9     cin >> num1;
10    cout << "Enter the second number: ";
11    cin >> num2;
12    cout << "Enter the third number: ";
13    cin >> num3;
14    avg = num1 + num2 + num3 / 3;
15    cout << "The average is " << avg << endl;
16    return 0;
17 }

```

num1	num2	num3	avg
?	?	?	?
?	?	?	?
10	?	?	?
10	?	?	?
10	20	?	?
10	20	?	?
10	20	30	?
10	20	30	40
10	20	30	40

Addison-Wesley
3x51mp1r1of

PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

3.11

A Case Study

Addison-Wesley
3x51mp1r1of

PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

A Case Study

- General Crates, Inc. builds custom-designed wooden crates.
- You have been asked to write a program that calculates the:
 - Volume (in cubic feet)
 - Cost
 - Customer price
 - Profit of any crate GCI builds

Addison-Wesley
3x51mp1r1of

PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Variables

Table 3-14

Constant or Variable	Description
COST_PER_CUBIC_FOOT	A named constant, declared as a double and initialized with the value 0.23. This represents the cost to build a crate, per cubic foot.
CHARGE_PER_CUBIC_FOOT	A named constant, declared as a double and initialized with the value 0.5. This represents the amount charged for a crate, per cubic foot.
length	A double variable to hold the length of the crate, which is input by the user.
width	A double variable to hold the width of the crate, which is input by the user.
height	A double variable to hold the height of the crate, which is input by the user.
volume	A double variable to hold the volume of the crate. The value stored in this variable is calculated.
cost	A double variable to hold the cost of building the crate. The value stored in this variable is calculated.
charge	A double variable to hold the amount charged to the customer for the crate. The value stored in this variable is calculated.
profit	A double variable to hold the profit GCI makes from the crate. The value stored in this variable is calculated.

Addison-Wesley
3x51mp1r1of

PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Program Design

The program must perform the following general steps:

- Step 1:
Ask the user to enter the dimensions of the crate
- Step 2:
Calculate:
the crate's volume
the cost of building the crate
the customer's charge
the profit made
- Step 3:
Display the data calculated in Step 2.


Addison-Wesley
3x51mp1r1of

PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

General Hierarchy Chart

Figure 3-7




Addison-Wesley
is an imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Get Crate Dimensions

Figure 3-8




Addison-Wesley
is an imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Calculate Volume, Cost, Customer Charge, and Profit

Figure 3-9




Addison-Wesley
is an imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Display Calculated Data

Figure 3-10



Addison-Wesley
is an imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Pseudocode

Ask the user to input the crate's length.
Ask the user to input the crate's width.
Ask the user to input the crate's height.
Calculate the crate's volume.
Calculate the cost of building the crate.
Calculate the customer's charge for the crate.
Calculate the profit made from the crate.
Display the crate's volume.
Display the cost of building the crate.
Display the customer's charge for the crate.
Display the profit made from the crate.

Addison-Wesley
is an imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Calculations

The following formulas will be used to calculate the crate's volume, cost, charge, and profit:

$$\text{volume} = \text{length} \times \text{width} \times \text{height}$$

$$\text{cost} = \text{volume} \times 0.23$$

$$\text{charge} = \text{volume} \times 0.5$$

$$\text{profit} = \text{charge} - \text{cost}$$

Addison-Wesley
is an imprint of
PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

The Program

Program 3-28

```

1 // This program is used by General Crates, Inc. to calculate
2 // the volume, cost, customer charge, and profit of a crate
3 // of any size. It calculates this data from user input, which
4 // consists of the dimensions of the crate.
5 #include <iostream>
6 #include <iomanip>
7 using namespace std;
8
9 int main()
10 {
11     // Constants for cost and amount charged
12     const double COST_PER_CUBIC_FOOT = 0.21;
13     const double CHARGE_PER_CUBIC_FOOT = 0.1;
14
15     // Variables
16     double length, // The crate's length
17           width, // The crate's width
18           height, // The crate's height
19           volume, // The volume of the crate
20           cost, // The cost to build the crate
21           charge, // The customer charge for the crate
22           profit; // The profit made on the crate
23
24     // Set the desired output formatting for numbers.
25     cout << setprecision(2) << fixed << showpoint;
26

```

Addison-Wesley
Learning Technology

PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Continued...

The Program

```

27 // Prompt the user for the crate's length, width, and height
28 cout << "Enter the dimensions of the crate (in feet):\n";
29 cout << "Length: ";
30 cin >> length;
31 cout << "Width: ";
32 cin >> width;
33 cout << "Height: ";
34 cin >> height;
35
36 // Calculate the crate's volume, the cost to produce it,
37 // the charge to the customer, and the profit.
38 volume = length * width * height;
39 cost = volume * COST_PER_CUBIC_FOOT;
40 charge = volume * CHARGE_PER_CUBIC_FOOT;
41 profit = charge - cost;
42
43 // Display the calculated data.
44 cout << "The volume of the crate is ";
45 cout << volume << " cubic feet.\n";
46 cout << "Cost to build: $" << cost << endl;
47 cout << "Charge to customer: $" << charge << endl;
48 cout << "Profit: $" << profit << endl;
49 return 0;
50 }

```

Addison-Wesley
Learning Technology

PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.

Continued...

The Program

Program Output with Example Input Shown in Bold

```

Enter the dimensions of the crate (in feet):
Length: 10 [Enter]
Width: 8 [Enter]
Height: 4 [Enter]
The volume of the crate is 320.00 cubic feet.
Cost to build: $73.60
Charge to customer: $160.00
Profit: $86.40

```

Program Output with Different Example Input Shown in Bold

```

Enter the dimensions of the crate (in feet):
Length: 12.5 [Enter]
Width: 10.5 [Enter]
Height: 8 [Enter]
The volume of the crate is 1050.00 cubic feet.
Cost to build: $241.50
Charge to customer: $525.00
Profit: $283.50

```

Addison-Wesley
Learning Technology

PEARSON

Copyright © 2015, 2012, 2009 Pearson Education, Inc., Publishing as Addison-Wesley. All rights reserved.